



## SPECIFICATION OF PRINT READY PDF:S & EPS

Print ready PDFs or EPS must be saved with crop marks and bleeds. Resolution has to be 100dpi in a scale of 100%. Convert all text to outlines. Save the print ready PDF in PDF version 1.5.

Colour settings: Adobe RGB(1998)(RGB colorspace) and Coated FOGRA39(CMYK colorspace). Images are to be saved in RGB-mode with the profile Adobe RGB(1998) embedded. The documents color settings are to be saved in a CMYK-mode.

The name of the file shall include the product name and format. If a new file is uploaded to replace an old one, name the file v2 in the end.

### UPLOADING OF FILES

Files of 10MB or less are sent by e-mail to your contact person at TB Screen.  
Files over 10MB are uploaded on our FTP, please archive the files in one zip file.

### FTP DETAILS

Address: ftp.tbscreen.se  
Username: ftptb  
Password: tbscreen

After uploading files to the FTP server please send an e-mail to danne@tbscreen.se and attach a low resolution PDF.

### VINYL

Rear of bus  
Longside  
Boarding bus  
Boarding tram  
XL

### TRIMMED AREA

1395x495 mm  
3050x650 mm  
1395x495 mm  
2495x495 mm  
1700x745 mm

### VISABLE AREA

1375x475 mm  
3030x630 mm  
1375x475 mm  
2475x475 mm  
1680x725 mm

Contact persons at TB Screen

Daniel Agné, project manager  
0046 21 475 00 00  
danne@tbscreen.se

Per Karlsson, Account manager  
0046 21 475 00 00  
per@tbscreen.se